

Wedge & Threshold Ramps



Fig 4 - Rubber Wedge Ramp (RW6 - 48)



Fig 5 - Rubber/Composite Wedge Ramp (RWS22 - 51)

Fig 4 ▲ Rubber wedge ramps can be cut to size and are ideal for inside or outside use.

Fig 5 ▲ Rubber wedges with sloped sides which allows access from all angles.

Rubber Wedge Ramp	Height	Length	Width	Colour	SWL	Weight
RW6	0.25"/6mm	2.5"/60mm	35.5"/900mm	Grey	500kg	0.25kg
RW12	0.5"/12mm	4.75"/120mm	35.5"/900mm	Grey	500kg	0.75kg
RW24	1"/24mm	6"/150mm	35.5"/900mm	Grey	500kg	2kg
RW36	1.5"/36mm	8"/200mm	35.5"/900mm	Grey	500kg	2.5kg
RW48	2"/48mm	10"/250mm	35.5"/900mm	Grey	500kg	3kg

Rubber/Composite Sloped Wedge Ramp	Height	Length	Width	Colour	SWL	Weight
RWS22	0.9"/22mm	6"/150mm	42"/1070mm	Black	500kg	3.2kg
CWS32	1.3"/32mm	12"/310mm	42"/1070mm	Granite Grey/ Antique Bronze	500kg	5kg
RWS45	1.8"/45mm	18"/460mm	50"/1270mm	Black	500kg	18.2kg
RWS51	2.0"/51mm	24"/610mm	59.75"/1520mm	Black	500kg	34.1kg

Fig 6 ▶ Aluminium two piece design is capable of coping with rises between 1.25" (32mm) and 3" (75mm) approx. and allows a full 1.75" (45mm) variation in height from one side to the other.

Alum. Threshold Bridge Ramp	Length	Width	SWL	Weight
ATB80	22"/560mm	31.5"/800mm	500kg	7kg



Fig 6 - Threshold Bridge Ramp (ATB80)